## CALIBRE



# HQView630

HQUItra Events Scaler-Switcher with HQUItraFast Input Switching



HQView630 is a universal image scaler based on Calibre's proprietary class-leading HQUltra 4K image processing technology. HQUltra scaling provides best in class picture quality with low latency video processing.

Featuring Calibre's proprietary HQUItraFast input channel switching able to switch input channels in under a quarter of a second, HQView630 has a wide range of input connectivity for today's digitally connected ProAV world, but still is able to support legacy formats too, all with great image quality.

HQView630 includes front panel controls with easy to read front panel menu system as well as remote control via inbuilt webserver or easy to implement API commands.

For in-camera and broadcast use a Genlock input is provided compatible with bi or tri-level sync or black & burst.

Flexible Pan-Tilt-Zoom controls allow selection of an area of interest

Rugged 1U rack-mountable case with integral modular universal mains PSU.

- Perfect scaling with Calibre's HQUItra low-latency 4K best-in-class proprietary scaling algorithms
- HQUItraFast proprietary typical 0.25 seconds input channel switching technology
- · Front panel jog-wheel and LCD display for fast easy set-up in the field
- 10 Video Inputs: 2xHDMI 4K, 1xHDMI HD, 1xDisplayPort 4K, 2x3G-SDI, 1xVGA, 1xCVBS, 1xDVI-U (DVI/HDMI & VGA/RGBS/YPbPr)
- 3 Video Outputs: 1xHDMI 4K, 1xDVI/HDMI, 1x3G-SDI
- Picture in Picture
- Brightness, Contrast, Saturation controls for all source types
- RGB calibration controls (not 4:2:0 in to 4:2:0 out)
- Flexible Aspect Ratio Conversion
- Full Genlock and Source Lock for in-camera & broadcast applications
- Audio de-embed from HDMI, DisplayPort and 3G-SDI inputs to S/PDIF, re-embed to HDMI outputs
- Multiple outputs for local monitoring of live output feed
- Remote control via webserver or simple API
- Optional analogue audio, mic mixer and 30W RMS power amp
- Optional H.264 HD Streaming Video Input



Calibre UK Ltd, Cornwall House, Cornwall Terrace, Bradford, West Yorkshire BD8 7JS, UK proavsales@calibreuk.com +44 1274 940770 +1 438 448 3614 +86 95013 5890 6926 www.calibreuk.com



# HQView630

## Inputs

2x HDMI 4K

1x HDMI HD 1xDisplayPort 4K

2x 3G-SĎI 1x DVI-U supporting VESA modes, SD, HD, can be configured as fourth HDMI input. DVI-U input also simultaneously supports VGA/RGBS/YPbPr legacy analog formats with suitable cable.

1x VGA Analog 1x Composite PAL/NTSC/SECAM

1x Genlock reference sync input, supports bi/tri-level or black&burst 50/59.94/60Hz Optional H.264 Streaming Video Input via Gigabit Ethernet Port

HDCP supported on all HDMI/DVI/DisplayPort I/O

Supported digital input and output formats: 4K/UHD (HDMI 4K/DisplayPort /HDBaseT only) 4AVIDID (IDINI 4AVIDS)pi39/01 / IDIDBASE 1 011)/ 3840x2160p, 4096x2160p 23.97/24/25/29.94/30/50/59.94/60; UHD/4K 50/59.94/60p modes supported in 4:2:0 format. HD 1280x720p, 1920x1080j, 1920x1080psf, 1920x1080p23.97/24/25/29.94/30/50/59.94/60, 2048x1080p23.97/24/25/29.94/30/50/59.94/60. ED 480p, 576p (not via SDI), SD 625i (576i), 525i (480i) Common VESA graphics formats from VGA to 4K,

(Modes higher than WUXGA on 4K capable input channels only)

Note: Some 4K zoom functionality is limited/unavailable when PIP is in use

## **HQUItra Events Scaler-Switcher with HQUItraFast Input Switching**

## **Outputs**

1x HDMI 4K via HDMI connector

1x DVI/HDMI via DVI connector

TX S/PDIF digital audio via RCA

NB: 3G-SDI output is disabled with HDCP-encrypted input and also for incompatible of All outputs are otherwise available simultaneously, with the same image shown on ea

## Supported Switching & Sync Modes

HQUItraFast input Switching in Genlock and Free-Run modes Also supports Source Lock when HQUItraFast not required

## **User Controls**

Front panel jog-wheel and LCD menu display for fast set-up. Keypad for direct input selection and integral indicator LEDs. Remote control via RS232, TCP/IP API and Web Server. Gigabit Ethernet for webserver and remote control API

## **Power Requirements**

100-264VAC, 50W typical

3-years return to base warranty covers parts and labour.

Order Codes HQView630 – Order Code **H630** 

HQView630A with Analogue Audio – Order Code H630A HQView630SV with Streaming Video Input – Order Code H630SV



Model >	H210	H310	H320	H325	L530	H620	H625	H630	H670	H730	H770	L720	L725	L730	L770
Front LCD menu or OSD control	OSD	OSD	OSD	OSD	LCD										
HDMI 4K Inputs						<b>■</b> (2)									
HDMI HD Input				•	•	•	•	•	•	•	•	•	•	•	•
DVI/HDMI HD Input													•		
HDBaseT 4K Input															
DisplayPort 4K Input															
Component Input		BNCs	BNCs		BNCs	DVI-U									
Composite Input(s)					<b>■</b> (2)										
VGA Analog Input		DVI-I	DVI-I		•										
3G-SDI Input(s)								<b>■</b> (2)	<b>■</b> (2)	<b>■</b> (2)	<b>■</b> (2)			<b>■</b> (2)	<b>■</b> (2)
DVI / HDMI HD Output	•						•								
HDMI 4K Output															
HDBaseT 4K Output															
VGA Analog Output															
3G-SDI Output															
3G-SDI Audio embed/de-embed & SPDIF					-				•	-	-			-	-
HQV Processing	•														
HQUItra 4K Low-Latency Processing															
HQUItraFast High Speed Input Switching															
PIP															
TCP/IP Webserver & API Control	•	•		•	•	•	•		•	•	•	•	•		
Geometry Correction, 4-Corner, Rotate	•		•	•	•										
Mesh-based Warp, config via PC App															
Genlock - V-Lock															
Genlock – H&V or Crosslock								•		•				•	•
Pan, Zoom, Tilt	•	•	•	•			•			•	•	•	•		•
Edge Blending		•	•	•	•										
Edge Blend Black Level Correction				•	•										
Videowall mode with auto PTZ		•	•	•	•	•	•		•	•	•	•	•	•	•
LED Videowall Per-Edge Sizing										•	•				
Analogue Audio In, Out and Power Amp						Opt	Opt	Opt	Opt						
Opt: option fitted to models with "A" suffix	ļ					JPI	Эрг	Эрг	Эрг					ļ	<u> </u>
Streaming Video Input via Network Port															
Opt: option fitted to models with "SV" suffix	1	l				Opt	Opt	Opt	Opt			Opt	Opt	Opt	Opt

Calibre UK Ltd, Cornwall House, Cornwall Terrace, Bradford, West Yorkshire BD8 7JS, UK

proavsales@calibreuk.com +44 1274 940770 +1 438 448 3614 +86 95013 5890 6926 www.calibreuk.com