

HD-inline Vakuum-Förderer Modelle

Technische Daten und Leistung der Fiktech HD-Inline

| Model | A Schlauch | B Nennweite | C | D | E | F | G | H | I | P BSP | Luftverbrauch h [L/Min.] | Vakuum [kPa] @ 5,5 |
|----------------------|---------------|----------------|-----|-----|----|----|----|---|-----|----------|-----------------------------|-----------------------|
| AF6078A1 AF6058SS | 10 | 5 | 25 | 55 | 40 | 16 | 16 | 3 | 18 | 1/8" | 160 | 29,9 |
| AF6079A1 AF6059SS | 13 | 8 | 32 | 66 | 48 | 19 | 19 | 3 | 26 | 1/8" | 200 | 24,9 |
| AF6080A1 AF6060SS | 19 | 13 | 50 | 100 | 46 | 25 | 25 | 3 | 38 | 1/4" | 310 | 12,2 |
| AF6081A1 AF6061SS | 25 | 19 | 54 | 124 | 48 | 25 | 25 | 4 | 48 | 1/4" | 420 | 11 |
| AF6082A1 AF6062SS | 32 | 25 | 63 | 124 | 48 | 25 | 25 | 4 | 48 | 1/4" | 730 | 11 |
| AF6083A1 AF6063SS | 38 | 32 | 69 | 124 | 48 | 25 | 24 | 4 | 58 | 1/4" | 840 | 8,0 |
| AF6084A1 AF6064SS | 51 | 45 | 82 | 124 | 53 | 32 | 32 | 4 | 72 | 3/8" | 1.260 | 6,7 |
| AF6085A1 AF6065SS | 63 | 55 | 100 | 134 | 75 | 38 | 38 | 4 | 90 | 3/8" | 1.660 | 6,0 |
| AF6086A1 AF6066SS | 76 | 68 | 110 | 142 | 69 | 42 | 42 | 4 | 102 | 1/2" | 1.970 | 3,4 |

