

massimo®
Power for life



STAY CHARGED WITH
HITMAN



High Performance Automotive Battery

TECHNICAL SPECIFICATIONS

Product Name	Container Type	Ah Capacity	Acid volume (in Ltr.)	Weight in kg		Dimension (mm)			Warranty* in Months
				Charged	Gross	L	W	H	
MB350-20R/L	NS40	35	2.4	10	10.4	197	124	230	18+18
MB600-26L	NS50	60	4.4	17.9	18.6	259	174	223	18+18
MB700-26R/L	NS50	65	4.4	18.4	19.1	259	174	223	18+18
MB750-31R	NS70	75	5.6	21.2	22.1	304	173	224	18+18
MB800-R/L	NS70	80	5.8	22.1	23	304	173	224	18+18
MB900-41L	N100	90	8.0	27.2	28.4	412	174	234	18+18
MB1050-41L	N100	105	7.4	28.3	29.5	412	174	234	18+18
MB1300-51R	N120	130	9.9	38.5	40	487	180	254	18+18
MB1500-51R	N150	150	11.5	40	41.5	504	222	254	18+18
MB1800-52R	N200	180	15.9	49	50.5	515	275	244	18+18
MB2000-52R	N200	200	15.7	52.3	53.8	515	275	244	18+18

Tolerance : Weight .±3%, Dimension ±3mm
*Warranty : Conditions Apply.

KEY FEATURES

- Specially design Hybrid grid with purest active material.
- Special negative PE separators with 0.6mm glass matt.
- High cranking power & very low self dis-charge ratio.
- Specially designed to prevent from overcharging.
- Better resistance to both heat & vibration.

FACTORY CHARGE
HYBRID TECHNOLOGY



Toll Free No. : 1800 120 8283
www.massimobatteries.com
info@massimobatteries.com